

# Action Tooltips

Version 2.0.0 (27.6.2015)

## Contents

1 Overview .....	1
2 Compatibility .....	1
3 Installation.....	1
4 Configuration .....	1
5 Advanced settings .....	1
6 Example .....	2

## 1 Overview

**Action Tooltips** creates popup tooltip boxes for fields in QPR Portal action edit form, for e.g. user instructions for filling form. There are info logos for all fields where there are tooltips (see the chapter 6. Example). Tooltip appear when the mouse cursor is moved on top of field name or info logo. The tooltip may contain html formatting, such as bolding, underlining, colors, and different font sizes.

## 2 Compatibility

Compatible with QPR 2015.1.

## 3 Installation

Installation steps:

1. Apply **Action Tooltips.patch** to C:\ProgramData\QPR Software\QPR 2015\2015.1\Servers\Templates\WAS\ (or use **associationeditorview.tpl**). (more information for changing templates: <https://community.qpr.com/node/1681>)
2. Copy file **actiontooltips.tpl** to C:\ProgramData\QPR Software\QPR 2015\2015.1\Servers\Templates\WAS\Portal.
3. Copy **icon\_info.png** to C:\inetpub\wwwroot\qpr2015-1\qprsoftware\portal\images.
4. Configure the actiontooltips.tpl file (see the next chapter).
5. Clear portal template cache.

## 4 Configuration

Tooltip contents is stored in actiontooltips.tpl (in javascript JSON variable "tooltipdata"). The array contains objects (one per row) with following properties:

Attribute	Description
field	Action field name with spaces included (e.g. "Header", "Description", "Assigned to"). Look the spelling in QPR Portal.
formtype	Action type name (e.g. Comment, Lesson). Look the spelling in QPR Portal. This definition is needed because different action types may contains same fields and different tooltips may be desired.
modelid	QPR Metrics model id. Leave empty if not needed. This definition is needed to enable different tooltips for same action type depending on which Metrics model is open.
infotext	The tooltip text content. Any html coding may be used. Note the example configuration for e.g. Scandinavian characters and special formatting.

## 5 Advanced settings

Web developers can change tooltip behavior and graphical layout as follows:

- Tooltip behavior (e.g. position, appearance delay) may be changed with tooltip parameters by web developers (documentation: <http://api.jqueryui.com/tooltip>).
- The tooltip box has css class "ui-tooltip-content". Following css can be added to custom.css to e.g. increase font size (or make any other change):

```
.ui-tooltip-content {
font-size: 13px;
}
```

## 6 Example

Note the info icons for fields where there are tooltips.

QPR Portal - Demo User (qpr) - Internet Explorer
Action type: **Comment** ▼

### Description

Header:

Tooltip text Tooltip text Tooltip text Tooltip text Tooltip text  
 text Tooltip text Tooltip text Tooltip text Tooltip text  
 Tooltip text

### Categorization

Category: **Not categorized** ▼

### Linked to

Control (2) <Element>

Add
Remove

### Dates

Date stamp: Year:  Month:  Day:

### Publish To

Users of linked elements  
 Me only  
 Everyone  
 Selected users

Notify via e-mail

### Attachments

Add
Delete

Created by: -  
Last Modified by:-